



AMCI WIRELESS **MONITOR 1440**

Monitor 1440 intelligently gathers and stores real-time, remote field data (e.g. compressor data, end-device & engine data) enabling standard Modbus RTU protocols. In addition it also provides the ability to bring back pressure sensors, tank levels and other operating parameters to help provide the operational intelligence for your remote site.



INT +1 346 701 5711



www.amci-wireless.com




255 Pennbriht Drive, Suite 240
Houston, TX 77090 **OR**
2171 S Trenton Way, Suite 217,
Denver, CO 80231



salesmgmt@amci-wireless.com

INFORMATION

**WIRELESS1440
iPHONE & ANDROID
APP**



- 3.8 x 3.8 in. (96 x 96 mm)
- 12 oz (340 g)



- Required power inrush: 30 A for 1 ms @ 24 VDC
- Primary power range: 10 - 30 VDC
- Relative humidity: 5 to 95% non-condensing

**ENGINE OPERATION
DATA**



- | | |
|---------|------------------|
| CE | UL |
| 2017072 | ATEX Directive |
| E180220 | 2014/34/EU |
| 7/20/17 | EMC - 2014/30/EU |




- Analog Inputs
- Safe Input Channels
- 4 Input Channels
- Safe input voltage range between -0.5 V to +12 V

**OPERATOR
INTERFACE**



- 3 year warranty (36 months)




- Medium Resolution

**DIN-RAIL OR PANEL
MOUNT**



- Tech support available 24/7



- MODBUS Protocols