



## **ST6100 - C1D2**

ST-6100-C1D2 is a fixed geo-stationary satellite communications terminal that utilizes two-way satellite technology to alert you to your asset(s) operating status. This allows for informed decisions and optimized operations.



INT +1 346 701 5711



[www.amci-wireless.com](http://www.amci-wireless.com)



255 Pennbriht Drive, Suite 240  
Houston, TX 77090 **OR**  
2171 S Trenton Way, Suite 217,  
Denver, CO 80231



[salesmgmt@amci-wireless.com](mailto:salesmgmt@amci-wireless.com)



# INFORMATION

ON DEMAND REPORTING

GPS

MODBUS OR EXPANDED I/O

AMCi-Wireless SatAlarm®-Server

MODBUS OR EXPANDED I/O

CID2 CERTIFIED MODEL FOR HAZARDOUS SITES

WEATHERPROOF CONSTRUCTION


GAP FREE COVERAGE

INTEGRATED ANTENNAS (NO COAX), NO EXTERNAL ANTENNAS

WIRELESS1440 iPHONE & ANDROID APP



- Serial
- Digital
- Analog



- 5.0 x 5.0 x 1.9 in. (12.6 x 12.6 x 4.9 cm)
- 1.0 lbs. (0.46 kg)



- Time of day/Interval based reporting schedule
- Modbus RTU: configurable demands




- Satellite - Inmarsat  
Other - CE, FCC, IC, Anatel, CID2 hazardous locations



- Acquisition Time: 1 second (Hot) 29/30/36 seconds(Cold)
- Accuracy: 2 meters (CEP)
- Tracking: -163 dBm



- 3 year warranty (36 months)



- Operating Temperature: -40°C to +85°C
- Input voltage: 9 to 32VDC



- Tech support available 24/7